



www.sealking.ca

BEFORE

AFTER



IMPRESSED CONCRETE SEALER - DATA SHEET

DESCRIPTION

Seal King's Impressed Concrete Sealer is an acrylic-based system. It is specially formulated to enhance the impressed concrete leaving a glossy wet looking appearance. This Sealer will protect from oil, salt, dirt and discoloring. (Solids Content = 25%)

BENEFITS

- Protects against oil, dirt and salt
- Enhances color of concrete
- Leaves a glossy, wet look
- Makes cleaning easier
- Touch dry in 30 minutes, can be driven on after 4 hours

DIRECTIONS FOR APPLICATION

- Remove any oil, dirt and other contaminants with Seal King's cleaners.
- Make sure the area to be sealed is completely dry and clean (usually 24 hours without dampness).
- If surface was sealed previously, do a test sample by applying sealer on small area.
- Apply with roller or spray pump.

CAUTION

- Do not use indoors.
- This product contains flammable solvents, keep away from flames and heat. Do not smoke when applying this product.
- Avoid skin and eye contact, if contact occurs wash thoroughly with cold water.
- Avoid breathing vapors. Use adequate ventilation.

- Keep container closed when not in use.
- Store in cool dry place. Protect from freezing.
- Keep away from children.

PLEASE NOTE

- Read all instructions before use.
- Do not apply in temperatures below 7°C (45°F).
- Use Seal King's Grease Release to clean equipment.

COVERAGE

- Approximately 800 sq. ft./5 gal

V.O.C. COMPLIANT

Product meets V.O.C. contents in accordance to E.P.A. 40 CFR pt 59 table I subpart D for Concrete Curing & Sealing Compounds with maximum V.O.C. content of **400 G/L.**

SIZES AVAILABLE:

FINISHES:

WATER BOURNE (WB):

WB FINISHES:

5 gal. (18.9 Ltr), 1 gal. (3.78 Ltr)

Wet Look

Available

Wet look