

Wilfrid Slab




- Do not use vibrating plate
- Pedestrian - Designed to withstand pedestrian traffic
- Techniseal** 1 bag of sand covers approx. 244 ft²


Wilfrid Slab

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
A	A 60 x 570 x 380	2 3/8 x 22 7/16 x 15	PRESTIGE COLOURS		
B	B 60 x 570 x 570	2 3/8 x 22 7/16 x 22 7/16	12051189	Range Amber Beige	
C	C 60 x 570 x 950	2 3/8 x 22 7/16 x 37 3/8	12051213	Range Scandina Grey	
	Weight/unit (avg.)	53 kg	117 lb		
	Surface/unit (avg.)	1.08 m ²	11.66 ft ²		
	Area/cube	9.72 m²	9 Rows	104.94 ft²	
	Weight/cube	1422 kg	3150 lb		
			Production location Cambridge		

LAYING PATTERNS



Modular



Linear

TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
Wilfrid Slab	CSA A231.1	±4.5 MPa	N/A	225 g/m ² after 28 cycles 500 g/m ² after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

* Concave or convex warpage in one dimension: up to and including 450 mm: 2.0 mm / over 450 mm: 3.00 mm

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.